

Date: Tuesday, 12/5/2006 8:16:26 AM
 User: Kim Johnston

Process Sheet

Customer : CU-DAR001 Dart Helicopters Services Drawing Name : 206/OH-58 SADDLE, INBOARD, RIGHT SIDE
 Job Number : 29790
 Estimate Number : 10834
 P.O. Number : N/A Part Number : D29332
 This Issue : 12/5/2006 S.O. No. : N/A Drawing Number : D2933 UNDER REVIEW
 Prsht Rev. : NC Project Number : N/A
 First Issue : N/A Type : MACHINED PARTS Drawing Revision : B
 Previous Run : 29233 Material : N/A
 Due Date : 12/23/2006 Qty: 8 Um: Each
 Written By :
 Checked & Approved By :
 Comment : Est: B 000626 New DWG rev (mpp 2069) EC

Additional Product

Job Number:



Seq. #: Machine Or Operation: Description :

1.0 D6101001 7075-T7351 2X6X6.25



Comment: Qty.: 1.0000 Each(s)/Unit Total : 8.0000 Each(s)
 Issue material from stock: 7075-T7351 QQ-A-250/12
 Cut Size 2.0 x 6.25 X 6.00
 Grain Along Long 6.00 Length
 Batch No: B25345

ml 06/12/19

8

2.0 HAAS1 HAAS CNC VERTICAL MACHINING #1



Comment: HAAS CNC VERTICAL MACHINING #1
 Program part number and batch number.
 1-Inspect part number and batch number are programmed correctly.
 2-Machine Step No 1 of Folio and visually inspect as per dwg D2933 & attached Dimension Sheet
 3-Machine Step No 2 of Folio and visually inspect as per dwg D2933 & attached Dimension Sheet
 4-Machine Step No 3 of Folio and visually inspect as per dwg D2933 & attached Dimension Sheet
 5-Deburr

ml 06/12/20

8

3.0 MILLING CONV. CONVENTIONAL MILLING MACHINE



Comment: CONVENTIONAL MILLING MACHINE
 Machine Keyway and inspect per attached dimension sheet

ml 06/12/20

8

4.0 QC1 INSPECT ALL DIM TO DIM SHEET



Comment: INSPECT ALL DIM TO DIM SHEET

ml 06/12/20

8

W/O:		WORK ORDER CHANGES						
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector	
06.12.05	2	Tooling to Tool rad for Flange pockets should be R0.188 INSTEAD OF R0.25-R0.30. -Ref attached DS email				CP 06.12.05 P 08/042		

Part No: _____ PAR #: _____ Fault Category: _____ NCR: Yes ☒ No ☐ DQA: D Date: 06.12.05
 QA: N/C Closed: _____ Date: _____

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries

Date: Tuesday, 12/5/2006 8:16:26 AM
User: Kim Johnston

Process Sheet

Customer: CU-DAR001 Dart Helicopters Services

Drawing Name: 206/OH-58 SADDLE, INBOARD, RIGHT SIDE

Job Number: 29790

Part Number: D29332

Job Number:



Seq. #:

Machine Or Operation:

Description :

5.0

QC8

SECOND CHECK



Comment: SECOND CHECK

En 06/12/20 x (8)

6.0

HAND FINISHING1

HAND FINISHING RESOURCE #1



Comment: HAND FINISHING RESOURCE #1

Acid etch and Alodine as per QSI 005 4.1

M-H / a.m

06/12/21 (8)

7.0

POWDER COATING

POWDER COATING



Comment: POWDER COATING

Powder Coat White Gloss (Ref: 4.3.5.1) as per QSI 005 4.3

M 102 39 / a.m

06/12/22 (PY)

8.0

QC3

INSPECT POWDER COAT/CHEMICAL CONVERSION



Comment: INSPECT POWDER COAT

12/4/22 (8)

9.0

PACKAGING 1

PACKAGING RESOURCE #1



Comment: PACKAGING RESOURCE #1

Identify and Stock

Location: 51475

12/4/22 (8)
06/12/22 (8)

10.0

QC21

FINAL INSPECTION/W/O RELEASE



Comment: FINAL INSPECTION/W/O RELEASE

12/06/12/22

Job Completion



12/06/12/22

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: _____ PAR #: _____ Fault Category: _____ NCR: Yes No DQA: _____ Date: _____

QA: N/C Closed: _____ Date: _____

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries

DART AEROSPACE LTD	Work Order:	29790
Description: 206 Saddle, Inboard, Right side	Part Number:	D2933-2
Inspection Dwg: D2933 Rev. B		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2933 Rev. B and record below:

				Recorded Actual Dimensions					
Dim	Min	Max	Go/No Go Gauge	1	2	3	4	By	Date
A	0.100	0.140		0.122	0.124	0.122	0.121		
B	0.100	0.140		0.120	0.124	0.121	0.121		
C	0.100	0.140		0.130	0.127	0.126	0.120		
D	0.210	0.230		0.219	0.221	0.220	0.221		
E	1.245	1.255		1.250	1.250	1.250	1.250		
F	1.245	1.255		1.250	1.250	1.250	1.250		
G	2.495	2.505		2.500	2.500	2.499	2.500		
H	0.510	0.515		0.512	0.512	0.512	0.512		
I	1.572	1.582		1.576	1.577	1.577	1.576		
J	2.495	2.505		2.500	2.500	2.499	2.500		
K	0.257	0.262	DT8683	0.259	0.259	0.259	0.259		
L	0.312	0.317	DT8686	0.314	0.314	0.314	0.314		
M	0.235	0.240		0.236	0.237	0.236	0.236		
N	0.100	0.140		0.121	0.121	0.121	0.121		
O	0.540	0.560		0.547	0.550	0.550	0.551		
P	0.490	0.510		0.502	0.503	0.503	0.503		
Q	3.715	3.725		3.718	3.718	3.718	3.717		
R	2.470	2.510		2.495	2.503	2.495	2.500		
S	0.240	0.270		0.250	0.252	0.251	0.249		
T	0.100	0.180		0.140	0.142	0.143	0.143		
U	1.625	1.635		1.630	1.630	1.630	1.630		
V	1.362	1.372		1.365	1.367	1.366	1.366		
W	0.316	0.321	DT8690	0.320	0.320	0.320	0.319		
X	1.125	1.145		1.131	1.136	1.135	1.136		
Y	1.565	1.585	DT8695 A/B	1.567	1.567	1.569	1.577		
Z									
AA									
AB									
AC									
AD									
AE									
AF									
AG									
AH									
Accept/Reject									

Measured by:	<i>anf</i>
Date:	06/12/20

Audited by:	<i>En</i>
Date:	06/12/20

Rev	Date	Change	Revised by	Approved
A		New Issue	RF	
B	02.12.12	Re-format; Added Dim. X-Y, DT8683, DT8686, DT8690 & DT8695 A/B	KJ/RF <i>TH</i>	<i>#</i>

DART AEROSPACE LTD	Work Order:	29790
Description: 206 Saddle, Inboard, Right side	Part Number:	D2933-2
Inspection Dwg: D2933 Rev. B		Page 1 of 1


Inspect dimensions highlighted on inspection sheet drawing D2933 Rev. B and record below:

				Recorded Actual Dimensions					
Dim	Min	Max	Go/No Go Gauge	1	2	3	4	By	Date
A	0.100	0.140		0.122	0.121	0.121	0.122		
B	0.100	0.140		0.121	0.121	0.121	0.121		
C	0.100	0.140		0.125	0.125	0.128	0.129		
D	0.210	0.230		0.221	0.221	0.221	0.221		
E	1.245	1.255		1.246	1.250	1.249	1.249		
F	1.245	1.255		1.250	1.250	1.249	1.250		
G	2.495	2.505		2.500	2.500	2.500	2.500		
H	0.510	0.515		0.512	0.512	0.512	0.512		
I	1.572	1.582		1.576	1.576	1.577	1.578		
J	2.495	2.505		2.500	2.500	2.500	2.500		
K	0.257	0.262	DT8683	0.259	0.259	0.259	0.289		
L	0.312	0.317	DT8686	0.314	0.314	0.314	0.314		
M	0.235	0.240		0.236	0.236	0.236	0.236		
N	0.100	0.140		0.122	0.121	0.121	0.121		
O	0.540	0.560		0.552	0.550	0.551	0.551		
P	0.490	0.510		0.505	0.504	0.505	0.504		
Q	3.715	3.725		3.717	3.718	3.718	3.719		
R	2.470	2.510		2.499	2.499	2.497	2.497		
S	0.240	0.270		0.251	0.251	0.249	0.247		
T	0.100	0.180		0.145	0.143	0.146	0.145		
U	1.625	1.635		1.629	1.631	1.630	1.629		
V	1.362	1.372		1.366	1.366	1.367	1.366		
W	0.316	0.321	DT8690	0.320	0.320	0.320	0.320		
X	1.125	1.145		1.135	1.135	1.135	1.136		
Y	1.565	1.585	DT8695 A/B	1.571	1.573	1.574	1.575		
Z									
AA									
AB									
AC									
AD									
AE									
AF									
AG									
AH									
Accept/Reject									


Measured by:	amf
Date:	06/12/20

Audited by:	E
Date:	06/12/20

Rev	Date	Change	Revised by	Approved
A		New Issue	RF	
B	02.12.12	Re-format; Added Dim. X-Y, DT8683, DT8686, DT8690 & DT8695 A/B	KJ/RF <i>[initials]</i>	<i>[initials]</i>



SHOP COPY
RETURN TO
ENGINEERING
UNCONTROLLED COPY
SUBJECT TO AMENDMENT
WITHOUT NOTICE
WORK ORDER
NO. 29790

B	00.05.29	CHANGED GEOMETRY AND MATERIAL
A	99.10.29	NEW ISSUE
DESIGN #	DRAWN BY RF	 DART AEROSPACE USA, INC. BELLUQUE, WA
CHECKED #	APPROVED #	
DATE 00.05.29	DRAWING NO. D2933 TITLE: SADDLE INSIDE SCALE: 2:1 REV. 5 SHEET 1 OF 1	

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL
AND IS SUPPLIED ON THE EXPRESS CONDITION
THAT IT IS NOT TO BE USED FOR ANY PURPOSE
OR COPIED OR COMMUNICATED TO ANY OTHER
PERSON WITHOUT WRITTEN PERMISSION FROM
DART AEROSPACE USA, INC.

Chris Provencal

From: David Shepherd [dshepherd@dartaero.com]
Sent: October 19, 2006 3:31 PM
To: 'S Shahbazian'
Cc: 'Provencal, Chris'; 'Charbonneau, Eric'
Subject: RE: Radius dimension on the saddle

Change the drawings. I guess we will also change the 0.313 crosstube hole dimensions as well.
See D2661 to D2668 as well as D2932 to D2933.

David

From: S Shahbazian [mailto:sshahbazian@dartaero.com]
Sent: Thursday, October 19, 2006 1:16 PM
To: Shepherd, David
Cc: Provencal, Chris; Charbonneau, Eric
Subject: Radius dimension on the saddle

Dave,
On attach saddle drawing, according to Eric the marked-up radius that reads 0.30 and 0.25, should be 0.188 since the tooling has been changed long time ago, and apparently they have been machining those radiuses to 0.188 for a while. Do you see a problem with that? if not I will go ahead and change the drawing to reflect the changes.

Serge

--
No virus found in this incoming message.
Checked by AVG Free Edition.
Version: 7.1.408 / Virus Database: 268.13.7/488 - Release Date: 10/19/2006

--
No virus found in this outgoing message.
Checked by AVG Free Edition.
Version: 7.1.408 / Virus Database: 268.13.7/488 - Release Date: 10/19/2006

05/12/2006